

®  
**FIBERWEB**

®  
***AQUA FLASH***

**LATEX PRIMER**

---

### **DESCRIPTION**

AQUA FLASH Primer is a one component water-based high tack primer specifically designed to promote maximum adhesion of the AQUA FLASH waterproofing membrane on all vertical and horizontal surfaces. May be applied to concrete, block, brick wood, metal, and gypsum.

### **APPLICATION INSTRUCTIONS**

Substrate surface should be dry, free from oil and grease or any loose debris of any kind. Primer should be stirred in the container and applied either with a soft bristle brush or suitable spray equipment. Allow Primer to dry prior to application of the waterproofing membrane.

### **PHYSICAL PROPERTIES:**

Weight	9 lbs.
Total solids	49%
Dry time (75°F % 50% Humidity)	4 hrs.
Flammability (Wet)	Non-flammable
Application Temperature	>40°F

**SPECIFICATION:** Meets ASTM D 1227-82 TYPE III

**COVERAGE:** 50 square feet/gallon depending on the porosity and condition of the substrate

**CLEAN-UP:** Wet primer can be cleaned up with soap and water. If primer has dried, mineral spirits or paint thinner may be used

**Packaging:** 5 gallon

### **Storage**

Product needs to be stored above 40°F.

®  
**Product Information:** All users of the *AQUA FLASH* products should read the Safety Data Sheets (SDS) which are available from the manufacturer listed below or visit [www.fiberwebflashing.com](http://www.fiberwebflashing.com).  
Contact a FIBERWEB representative or our offices with any questions.

**FIBERWEB**     ***AQUA FLASH***

**DIVISION OF**

Clark/Hammerbeam Corp.

PO Box 381

Dedham, MA 02027

Tel. 781-461-1946

[www.fiberwebflashing.com](http://www.fiberwebflashing.com)