

FIBERWEB

DATA SHEET

®

BOND-N-FLASH PRIMER

Winter grade

Description: **BOND-N-FLASH Primer** is a solvent based primer specifically formulated for harsh winter temperatures and difficult substrate surfaces. It is used to enhance the permanent adhesion of the **BOND-N-FLASH** stainless steel membrane to all horizontal and vertical surfaces. **BOND-N-FLASH** Primer provides an immediate grab surface for the **BOND-N-FLASH** membrane establishing a fusion between the primer and the membrane.

Uses: Establishes a clean and superior bonding surface for the **BOND-N-FLASH** membrane promoting the longevity of the flashing. May be used on concrete, masonry, metal, and wood.

Features:

- Dries clear when ready for membrane installation
- High moisture resistance
- Fuses with applied membrane
- Extremely aggressive tack hold

Application: Apply **BOND-N-FLASH** Primer to a surface that is dry, clean and free of dust. Substrate should also be free of any oils, waxes and loose debris. Concrete surfaces should be cured prior to the application of the primer. Use either a brush or a short nap roller to apply the primer in a uniform fashion. Allow primer to turn from translucent midnight blue to transparent. (approximately 30 min.- 1 hr. @ 70 degrees) depending on temperature and humidity levels. Primer should be dry before applying the membrane (may be tacky but should not transfer to the fingers when touched). Premature application of membrane onto wet primer will smother tack development. Application temperature 32 degrees F and rising.

Coverage: The amount of **BOND-N-FLASH** Primer will vary widely from job to job. One gallon of **BOND-N-FLASH** Primer will cover approximately 250 square feet depending upon the porosity of the substrate.

Properties:

Description: Liquid

Base: : Acrylic

Color : Translucent Dark Blue-Wet
Transparent- Dry

Packaging:

Available in five (4) gallon pails

Storage: Store indoors. Protect from freezing.

Safety: Use gloves. May cause skin sensitization. Avoid breathing mist/vapors/spray. See MSDS for additional information prior to use.