

FIBERWEB DIV.
CLARK/HAMMERBEAM CORPORATION
PO BOX 381
886 WASHINGTON STREET
DEDHAM, MA 02027

LEED Product Qualification Data
Thermal & Moisture Protection
Flexible Membrane Flashing 07 65 00

Date: January 31, 2018

Project:

BOND-N-FLASH[®] Flexible Stainless Steel Flashing meets the following criteria for MR 4.1:
Composition of product: a layer of stainless steel, layer of adhesive, a layer of fabric film

Stainless Steel	02% Virgin Material
Stainless Steel	20% Post Industrial Recycled Content
Adhesive Compound	22% Virgin Material
Poly-Fabric Film	45% Virgin Material
Poly-Fabric Film	11% Post Industrial Recycled Content

Total Post- Industrial Recycled Content 31%

BOND-N-FLASH: Flexible Stainless Steel Flashing meets the following criteria for MR 5.1 and 5.2:

If within a 500 mile radius of our plants:

Clark/Hammerbeam Corporation
Cleveland, OH 44112

EMBODIED ENERGY:

Product does not use an adhesive which needs to be stored in a liquid state which requires a constant 24 hr. energy usage.

Note: In the above LEED Rating System are suggested applications of the BOND-N-FLASH stainless steel flashing. LEED applicants should determine the products qualities for their own LEED certification application

LEED is a registered trademark of the United States Green Building Council